

ISEO 20



MANUFACTURING & MACHINE TOOLS



Compressed air applications

APPLICATIONS

For general purpose compressed air applications as pneumatic tools and any other industrial applications.

ADVANTAGES

- † Good economical solution.
- † Customized branding on request.

TECHNICAL DESCRIPTION

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: SBR, black, smooth.

Temperature range: - 30°C to +70°C.

COMPLEMENTARY INFORMATION


Sold only by pallet.
Special prices for full truck and 1/2 truck.



TRELLEBORG



ISEO 20





ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
6.0 ±0.4	14.0 ±0.5	20	60	0.2	40	5503330	☒
6.0 ±0.4	14.0 ±0.5	20	60	0.2	80	5503531	☒
6.0 ±0.4	14.0 ±0.5	20	60	0.2	100	5503347	☐
8.0 ±0.6	17.0 ±0.6	20	60	0.27	40	5503332	☒
8.0 ±0.6	17.0 ±0.6	20	60	0.27	80	5503532	☒
8.0 ±0.6	17.0 ±0.6	20	60	0.27	100	5503350	☐
10.0 ±0.5	19.0 ±0.6	20	60	0.32	40	5503334	☒
10.0 ±0.5	19.0 ±0.6	20	60	0.32	80	5503533	☒
10.0 ±0.5	19.0 ±0.6	20	60	0.32	100	5503353	☐
13.4 ±0.6	23.0 ±0.7	20	60	0.43	40	5503336	☒
13.4 ±0.6	23.0 ±0.7	20	60	0.43	80	5503534	☐
13.4 ±0.6	23.0 ±0.7	20	60	0.43	100	5503356	☐
16.4 ±0.7	25.6 ±0.8	20	60	0.42	40	5503338	☒
16.4 ±0.7	25.6 ±0.8	20	60	0.42	80	5503535	☐
16.4 ±0.7	25.6 ±0.8	20	60	0.42	100	5503359	☐
19.4 ±0.8	30.5 ±1.1	20	60	0.68	40	5503340	☒
19.4 ±0.8	30.5 ±1.1	20	60	0.68	80	5503536	☐
19.4 ±0.8	30.5 ±1.1	20	60	0.68	100	5503362	☐
25.0 ±1.0	38.0 ±1.1	20	60	1	40	5503342	☒
25.0 ±1.0	38.0 ±1.1	20	60	1	80	5503537	☐
25.0 ±1.0	38.0 ±1.1	20	60	1	100	5503365	☐

Tolerance on length: ±1% (ISO 1307 Standard).

☒ Upon availability.



TRELLEBORG