

SSTE COMPOSITE CHEMICAL HOSE

APPLICATIONS:

COMPOSITE CHEMICAL HOSE SSTE

Recommended for the delivery and/or suction of a wide range of chemicals and solvents. Contact your Fuel Flex application engineer for the correct choice of composite hose for your application.



FUEL FLEX SSTE

Standard series: SSTE TYPE 2
Heavy series: SSTE TYPE 3

Construction
Inner wire spiral: Stainless Steel (S)
Outer wire spiral: Stainless Steel (S)
Inner lining: PTFE (TE)
Cover: Polyester Fabric PVC-coated

Temperature Range: -20°C to +80°C

Standard / Approval: ISO 9001:2015

Work Safety Factor: The working pressure is based on a safety factor of 4:1



Code	Working pressure		Diameter	Bend radius	Weight	Maximum coil lengths
	Bar	Psi				
Fuel Flex SSTE TYPE 2 - Standard Duty						
SSTE25	10	150	1	68	1.6	15
SSTE40	10	150	1½	105	1.8	15
SSTE50	10	150	2	190	2.2	15
SSTE65	10	150	2½	225	2.8	15
SSTE80	10	150	3	290	3.6	15
SSTE100	10	150	4	320	4.3	15
Fuel Flex SSTE TYPE 3 - Heavy Duty						
SSTE25	14	203	1	68	1.8	15
SSTE40	14	203	1½	105	2.2	15
SSTE50	14	203	2	190	2.9	15
SSTE65	14	203	2½	225	3.2	15
SSTE80	14	203	3	290	3.8	15
SSTE100	14	203	4	320	4.8	15

DISCLAIMER: Should incorrect information be supplied by the customer, Fuel-Flex will not be held responsible for any failures and/or damage.

Fuel Flex (Pty) Ltd

Company Reg - 2005/006062/07 VAT No - 4700230602

16 Borax Street Alrode Ext 7, 1451 Gauteng, South Africa
PO Box 15558, Farrarmere, 1518, Benoni, South Africa

t: +27 (0) 11 826 5618 sales@fuelflex.co.za www.fuelflex.co.za

