



TECHNICAL SPECIFICATION SHEET



AAVR COMPOSITE VAPOUR HOSE

Document number: SF FF 122

Doc. revision number: 01

Revision date: 5/11/2018

Page: 1 of 1

APPLICATIONS:

FUEL-FLEX COMPOSITE VAPOUR HOSE AAVR

Recommended for Vapour recovery Applications
Due to its aluminium wire spiral, it is significantly lighter and easier to handle, especially in large diameters. This makes it ideal for use with tanker trucks, rail cars or fixed at depots.



FUEL-FLEX AAVR

Light Series: AAVR TYPE 2

Construction: Inner wire spiral: Aluminium (A)
Outer wire spiral: Aluminium (A)
Inner lining: Polypropylene (P)
Cover: Polyester Fabric PVC-coated

Temperature Range: -20°C to +80°C

Standard / Approval: ISO 9001:2015

Work Safety Factor: The working pressure is based on a safety factor of 3:1

CODE	Working Pressure		Diameter	Bend Radius	Weight	Maximum Coil Lengths
	(bar)	(Psi)				
Fuel-Flex AAVR TYPE 2 – Light Duty						
AAVR80	7	100	3	290	2.1	11
AAVR100	7	100	4	320	2.6	11

DISCLAIMER: Should incorrect information be supplied by the customer, Fuel-Flex will not be held responsible for any failures and/or damage.

FUEL-FLEX (PTY) LTD

PO Box 681, Honeydew, 2040, Johannesburg, South Africa
1504 Zeiss Road, Lazer Park, Honeydew, 1724, Gauteng, South Africa
Tel: +27 (0) 11 826 5618 Fax: +27 (0) 11 826 5681 www.fuelflex.co.za

