

EN 13765 - AAPH COMPOSITE FUEL HOSE

APPLICATIONS:

FUEL FLEX EN 13765 COMPOSITE FUEL HOSE AAPH

Recommended for the delivery and/or suction of a wide range of chemicals and solvents. Contact your Fuel Flex application engineer for the correct choice of composite hose for your application.



FUEL FLEX AAPH

Standard series: EN10AAPH TYPE 2
Heavy series: (Not available)

Construction
Inner wire spiral: Aluminium (A)
Outer wire spiral: Aluminium (A)
Inner lining: Polypropylene (P)
Cover: Polyester Fabric PVC-coated

Temperature Range: -20°C to +80°C

Standard / Approval: BS EN 13765:2010 + A1:2015

Work Safety Factor: The working pressure is based on a safety factor of 4:1



Code	Working pressure		Diameter	Bend radius	Weight	Maximum coil lengths
	Bar	Psi				
Fuel Flex AAPH TYPE 2 - Standard Duty						
EN10AAPH25	10	150	1	68	0.9	11
EN10AAPH40	10	150	1½	105	1.3	11
EN10AAPH50	10	150	2	190	1.6	11
EN10AAPH65	10	150	2½	225	1.8	11
EN10AAPH80	10	150	3	290	2.1	15
EN10AAPH100	10	150	4	320	2.6	15

DISCLAIMER: Should incorrect information be supplied by the customer, Fuel-Flex will not be held responsible for any failures and/or damage.

Fuel Flex (Pty) Ltd

Company Reg - 2005/006062/07 VAT No - 4700230602

16 Borax Street Alrode Ext 7, 1451 Gauteng, South Africa
PO Box 15558, Farrarmere, 1518, Benoni, South Africa

t: +27 (0) 11 826 5618 sales@fuelflex.co.za www.fuelflex.co.za

