

EN 13765 - GAPH COMPOSITE FUEL HOSE

APPLICATIONS:

FUEL FLEX EN 13765 COMPOSITE FUEL HOSE GAPH

Recommended for the delivery and/or suction of a wide range of chemicals and solvents. Contact your Fuel Flex application engineer for the correct choice of composite hose for your application.



FUEL FLEX GAPH

Standard series: EN10GAPH TYPE 2
Heavy series: (Not available)

Construction
Inner wire spiral: Galvanized (G)
Outer wire spiral: Aluminium (A)
Inner lining: Polypropylene (P)
Cover: Polyester Fabric PVC-coated

Temperature Range: -20°C to +80°C

Standard / Approval: BS EN 13765:2010 +A1:2015

Work Safety Factor: The working pressure is based on a safety factor of 4:1



Code	Working Pressure		Diameter	Bend radius	Weight	Maximum coil length
	Bar	Psi	"	mm	Kg/m	m
Fuel Flex GAPH - Standard Duty						
EN10GAPH25	10	150	1	68	1.1	15
EN10GAPH40	10	150	1½	105	1.4	15
EN10GAPH50	10	150	2	190	1.7	15
EN10GAPH65	10	150	2½	225	1.9	15
EN10GAPH80	10	150	3	290	2.4	15
EN10GAPH100	10	150	4	320	3.2	15
EN10GAPH150	10	150	6	365	5.3	15

DISCLAIMER: Should incorrect information be supplied by the customer, Fuel-Flex will not be held responsible for any failures and/or damages

Fuel Flex (Pty) Ltd

Company Reg - 2005/006062/07 | VAT No - 4700230602

6 Clarke Street, Alrode, Alberton, 1451, Gauteng, South Africa

PO Box 15558, Farrarmere, 1518, Benoni, South Africa

t: +27 (0) 11 826 5618

sales@fuelflex.co.za

www.fuelflex.co.za

