

EN 13765 - SSPP - COMPOSITE CHEMICAL HOSE

APPLICATIONS:

FUEL FLEX EN13765 SSPP COMPOSITE CHEMICAL HOSE

Recommended for the delivery and/or suction of a wide range of chemicals and solvents. Contact your Fuel Flex application engineer for the correct choice of composite hose for your application.



FUEL FLEX SSPP

Standard series: EN10SSPP TYPE 2
Heavy series: EN10SSPP TYPE 3

Construction Inner wire spiral: Stainless Steel (S)
Outer wire spiral: Stainless Steel (S)
Inner lining: Polypropylene (PP)
Cover: Polyester Fabric PVC-coated

Temperature Range: -20°C to +80°C

Standard / Approval: BS EN 13765:2010 +A1:2018

Work Safety Factor: The working pressure is based on a safety factor of 4:1



Code	Working Pressure		Diameter	Bend radius	Weight	Maximum coil length
	Bar	Psi	"	mm	Kg/m	m
Fuel Flex SSPP TYPE 2 - Standard Duty						
EN10SSPP25	10	150	1	68	1.6	15
EN10SSPP40	10	150	1½	105	1.8	15
EN10SSPP50	10	150	2	190	2.2	15
EN10SSPP65	10	150	2½	225	2.8	15
EN10SSPP80	10	150	3	290	3.6	15
EN10SSPP100	10	150	4	320	4.3	15
EN10SSPP150	10	150	6	365	6.8	15
Fuel Flex SSPP TYPE 3 - Heavy Duty						
EN14SSPP25	14	203	1	68	1.8	15
EN14SSPP40	14	203	1½	105	2.2	15
EN14SSPP50	14	203	2	190	2.9	15
EN14SSPP65	14	203	2½	225	3.2	15
EN14SSPP80	14	203	3	290	3.8	15
EN14SSPP100	14	203	4	320	4.8	15
EN14SSPP150	14	203	6	365	6.8	15

DISCLAIMER: Should incorrect information be supplied by the customer, Fuel-Flex will not be held responsible for any failures and/or damages

Fuel Flex (Pty) Ltd

Company Reg - 2005/006062/07 | VAT No - 4700230602

6 Clarke Street, Alrode, Alberton, 1451, Gauteng, South Africa

PO Box 15558, Farrarmere, 1518, Benoni, South Africa

t: +27 (0) 11 826 5618

sales@fuelflex.co.za

www.fuelflex.co.za

